



OPEN FRAME TYPE

DAISHIN GENERATOR

SEA & SEB SERIES

AVR



SEB3000Ha (60Hz)



SEB3000Ha (50Hz)

SEA3000Ha
SEB3000Ha

SEB6000Ha
SEB6000HSa

SEB7000Ha
SEB7000HSa

POWERED by **HONDA**

DAISHIN INDUSTRIES LTD.

with HONDA OHV Engine


Portable Generators

OPEN FRAME TYPE DAISHIN GENERATOR

Tough and durable open frame type generator with excellent AVR system



- Extremely durable "3D CURVE" steel control panel



- HONDA OHV 4-stroke engine GX series.




50Hz



60Hz


- Simple and easy operation control panel (50Hz/60Hz)

- Large fuel tank with protective bars
- Simplified module structure for easy maintenance




SEB7000Ha

- Low-tone large muffler




SGB7001Ha
(Made in JAPAN)



SEB7000Ha

- New design air cleaner



SGB7001Ha
(Made in JAPAN)

ACCESSORIES ● Instruction manual ● Engine manual ● Engine tool kit ● Plug heads for each receptacle ● Battery charge cable (except SEA3000Ha)

MODEL	SEA3000Ha	SEB3000Ha	SEB6000Ha	SEB6000HSa	SEB7000Ha	SEB7000HSa
Engine	HONDA					
Engine Brand	HONDA					
Engine Model	GX160	GX160	GX340	GX340	GX390	GX390
Displacement (cm ³)	163	163	337	337	389	389
Max. Output [kW(HP)/4000m ⁻¹]	4.0(5.5)	4.0(5.5)	8.1(11.0)	8.1(11.0)	9.6(13.0)	9.6(13.0)
Type	Air Cooled, 4-cycle, OHV Gasoline Engine					
Oil Alert System	N.A.	Standard				
Ignition System	Transistor (C.D.I.)					
Electric Start	N.A.		Standard		N.A.	Standard
Generator	Self-Exciting, 2-Pole, Field Rotating Type, Single Phase					
Alternator	AVR					
Voltage Regulator	Single					
Phase	Single					
AC Max. Output (kVA)	50Hz: 2.2 60Hz: 2.8	2.2 2.8	4.8 5.5	4.8 5.5	5.5 7.2	5.5 7.2
AC Rated Output (kVA)	50Hz: 2.0 60Hz: 2.4	2.0 2.4	4.0 4.5	4.0 4.5	5.0 6.1	5.0 6.1
Rated Voltage	220V 110/220V					
DC Output	N.A.					
Rated Power Factor	12V-8.3A (Receptacle) 1cosφ					
Other Features	Standard(except SEA3000Ha,110/220V,60Hz model)					
Pilot Lamp	Standard					
Volt Meter	N.A.					
Fuel Tank Capacity (ℓ)	3.6	16	25			
Continuous Operating Hours (hr:100%Load)	50Hz: 3.5 60Hz: 3.0	14.1 12.1	10.1 8.5	10.1 8.5	9.0 7.6	9.0 7.6
Measurement	685x534x509					
Dimensions (mm/LxWxH)	545x415x405	595x414x495	78.2	81.2	82.0	85.0
Dry Weight (kg)	35.0	45.8	128			
20Ft container Load	270	180				

*Specifications are subject to change without notice.



AGENT

DAISHIN INDUSTRIES LTD.

1520-1, Funatsuke, Yoro-cho, Yoro-gun, Gifu 503-1382 Japan
Phone 81-(0)584-36-0501 FAX 81-(0)584-36-0504
URL <http://www.daishin-japan.co.jp> E-mail overseas@daishin-japan.co.jp