

2GFCL



3GFCL



5GFCL



5GFCL E



*With Electric Starter

5GFLNE



*With Electric Starter
*Silent Type
*Battery

5GFLNE(2F)



*With 2 fans
*With Electric Starter
*Silent Type
*Battery

**FUEL PUMP
JAPAN FACTORY**



**CRANKCASE BEARING
NSK JAPAN**



SPECIFICATIONS

MODEL	2GFCL	3GFCL	5GFCL / 5GFCL E	5GFLNE / 5GFLNE(2F)
FREQUENCY (HZ)	50			
MAX. AC OUTPUT (KW)	1.9	3		5.5
RATED AC OUTPUT (KW)	1.8	2.8		5
DC OUTPUT (V-A)	12 / 8.3			
RATED VOLTAGE (V)	230 / 115			
RATED CURRENT (A)	7.8	12.2		21.7
RATED SPEED (r/min)	3600			
POWER FACTOR	1.0			
PHRASE	SINGLE PHRASE			
ENGINE MODEL	170F	178FA	186FA / 186FAE	
DISPLACEMENT (CC)	211	305	418	
RATED OUTPUT (ps/rpm)	3.4 / 3600	5.0 / 3600	8.85 / 3600	
FUEL TANK CAPACITY (L)	12.5			15