



WATER TRANSFER PUMPS

WP20 / WP30



**Trusted Power Equipment
For 100 Years.**

Milwaukee, USA



WATER TRANSFER PUMPS



1/C™ OHV Engine

- The small displacement engine with OHV design has the superior fuel and cooling efficiency. This allows for the correct power at low fuel consumption for your portable equipment.
- Dura-Bore™ cast iron sleeve improves its wear-resistance ability.
- The Lo-Tone® muffler allows for quiet operation.



Cast iron volute and impeller for long life and durability.



Self-suction Pumping fast operates easier.



Iso-mounts decrease vibration levels for unit stability and reduced component wear.



WP20

WP30

ENGINE		
Type	OHV 1/C®	OHV 1/C®
Displacement	127cc	163cc
Muffler	Lo-Tone®	Lo-Tone®
Fuel Tank Capacity (L)	2L	4L
PUMP		
Size inch (mm)	2" (50mm)	3" (80mm)
Discharge capacity	120 Gal/min	240 Gal/min
Gal./min. (L/min.)	(450L/min)	(900L/min)
Max Suction (m)	8m	8m
Total head lift (m)	33m	33m
PUMPSET		
Height (cm)	41.7cm	43.5cm
Depth (cm)	38cm	41.4cm
Width (cm)	48cm	50.7cm
Net weight (kg)	27kg	29kg
SPECIAL FEATURES		
Ignition system	Magnetron®	Magnetron®

PERFORMANCE

WP20



WP30

